



# TECHNICAL PAINT SERVICES

## AM60 GOLD POWDER IN PHENOLIC TUNG OIL

### **Features:**

A pure phenolic wood oil varnish, incorporating metallic gold powders. Ideally suited for interior decoration where there is a call for fine intricate decoration or for spraying large interior surfaces. It also has extremely good wear qualities and colour retention. For exterior decoration please use AM61.

### **Availability:**

5, 2.5 and 1 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

### **Volume Solids:**

53% ± 3% (BS 3900 Part A10).

### **Preparation:**

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

### **Application:**

By brush\* or conventional spray. On un-varnished wood (including worn surfaces), apply an initial sealer coat of AU109 Synthamel Undercoat in Yellow or Light Brown thinned up to 20% by volume with White Spirit, followed by one coat un-thinned, before application of AM60. If coats are applied at 24 hour intervals, it is not necessary to rub down between coats.

**\*NOTE:** Very small areas may be brush applied with the use of a fine, soft brush. Avoid brushing large areas as this will result in an uneven finish and colour distortion. This product must NOT be rolled.

### **Coverage:**

Approximately 60 metres per 5 Litres.

### **Drying:**

Touch dry: 4 hours @ 20°C.  
Hard dry: 8 hours @ 20°C.  
Recoatible: Overnight.

**Health & Safety:** Please see MSDS sheet 100D4.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

AM60 02 16

**FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.**

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255  
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.