

TECHNICAL PAINT SERVICES

## WBP185 WATER BASED HIGH BUILD METAL PRIMER

#### Features:

A high performance, water based, high build primer incorporating a chemical rust converter which exhibits excellent adhesion to ferrous and non ferrous substrates, affording a tough, durable coating. Suitable for application to substrates prior to application of water based acrylic finishes. Also suitable for use on structural steelwork not requiring over-coating.

## Availability:

5 Litre containers in Red Oxide and Grey. Please note our products are made to order and it may take 5-7 days before shipping.

### Volume Solids:

 $85\%\pm3\%$  (BS 3900 Part A10).

### Preparation:

Surfaces must be sound, clean, dry and free from wax, grease and oil. Remove all dust and loose particles. On existing painted surfaces, remove all loose and flaking paint and rub down thoroughly with abrasive paper. Any bare surfaces should be primed with a first coat.

### Application:

Stir thoroughly before use. Apply by brush, roller or spray. Do not apply at temperatures below 8°C, or when raining or foggy. For spraying, thin up to 20% with clean tap water. Ensure adequate ventilation during application and drying.

#### Coverage:

Approximately 8 - 12 sq metres per Litre depending on application method.

#### Drying:

, ,	
Touch dry:	1 hour @ 18°C and 65% humidity.
Recoatable:	Within 4 hours.

Health & Safety: Please see MSDS sheet 100C3.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

WBP185 04 14

# FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.