



TECHNICAL PAINT SERVICES

A148NS CHLORINATED RUBBER NON-SLIP SWIMMING POOL PAINT

Features:

A fast drying, Chlorinated Rubber Non-slip finish which due to its excellent scrub and chemical resistance, is ideally suited for steps and walkways in and around swimming pools. May be applied to concrete that has been newly laid and allowed to weather for 3 - 4 weeks.

Availability:

In 5 Litre containers. Standard colours are 18E50, 18E51, Black and White. Other BS4800 & RAL colours are also available as non-standard mixes. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

51% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease.

Application:

Brush or short pile thermally bonded roller. For new concrete, it is recommended that a first coat is applied thinned up to 10% by volume with UTR112 Universal Synthetic Thinners, followed by one or two coats as necessary, un-thinned. For application to wood, metal and fibreglass, please contact our Technical Department.

Coverage:

30-35 sq metres per 5 Litres per coat.

Drying:

Touch dry: 30 - 40 minutes @ 20°C.
3 hours @ 10°C.

Recoatable: 8 hours @ 20°C.
12 hours @ 10°C.

Note:

You **MUST** wait 5-7 days before filling the swimming pool so your new paint can cure completely. If there is rain during that time, remove any standing water after the rain has stopped. Use a sponge and leaf blower to dry the pool. If the rain lasts more than an hour or two, add a day to the cure time. After the cure time, fill the pool without stopping until the pool is full.

Health & Safety: Please see MSDS sheet **10019**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

A148NS 02 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.