



TECHNICAL PAINT SERVICES

A58 PLIOLITE BASED MASONRY COATING

Features:

A durable, weather resistant, Pliolite based coating with a low sheen finish which can be shower proof in one hour or less. Ideal for low temperature application. Suitable for application to cement rendering, concrete, brickwork, aqua board and wooden or cementitious Soffit boards. Can be used on high build textured finishes more than six months old. Ideal for walls or buildings that may need to be cleaned on a regular basis. Can be produced in a fine or medium gritted textured finish as a special mix.

Availability:

Most Pastel shades from the BS4800 range, in 5 Litre containers. Please contact our Technical Team for confirmation; other darker shades available with minimum 50 Litre batches. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

65% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease. Any loose, powdery or flaking paint should be removed with a wire brush. Fungus or mould should be scraped off and the surface treated with an Anti-Mould Wash. Concrete surfaces should be treated with AS56/5 Alkali Resisting Sealer White before application of A58 and must be at least six weeks old.

Application:

By brush or roller. Thin up to 10% by volume with UTR112 thinners for brushing. On rough or porous surfaces, two to three coats may be required and it is recommended that the first coat is thinned up to 10% by volume for ease of application when brushing, allowing overnight drying between coats. Must not be applied in temperatures below 4°C.

Coverage:

Approximately 30-40 sq. metres per 5 Litres per coat, depending on porosity of surface. Textured finish will be considerably lower at 20-30 sq. metres per 5 Litres per coat.

Drying:

Touch dry: 1 hour @ 10°C.
Recoatable: 2-4 hours depending on temperature.

Health & Safety: Please see MSDS sheet **100D4**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

A58 02 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.