



# TECHNICAL PAINT SERVICES

## A96 ROADLINE MARKING PAINT

### **Features:**

An extremely fast drying, durable finish suitable for application to concrete, tarmac, wood and most other surfaces. A96 exhibits excellent resistance to water, petrol, oil, grease and weak battery acid, and is also effective as a barrier coat where oil and grease stains on bitmastic surfaces have to be over-coated.

### **Availability:**

White, Black and Yellow in 5 Litre containers. Other colours available to order. Please note our products are made to order and it may take 5-7 days before shipping.

### **Volume Solids:**

55% ± 3% (BS 3900 Part A10).

### **Preparation:**

The substrate must be thoroughly clean, dry and free from dust and grease, although A96 will tolerate a small presence of oil and grease stains, it is recommended that where possible, these are removed.

### **Application:**

Brush or roller. Only use thermally bonded rollers. When brushing, apply with a lacquering action using as wide a brush as possible, as the finish is extremely fast drying.

### **Coverage:**

30 sq. metres per 5 Litres per coat @ 30 microns dry film thickness.

### **Drying:**

Touch dry: 30-60 minutes @ 20°C.

Hard dry: 2-4 hour @ 20°C.

**Health & Safety:** Please see MSDS sheet **10019**.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

A96 02 15

**FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.**

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255  
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.