



TECHNICAL PAINT SERVICES

CONTRACT GRADE EPOXY TWO PACK HIGH BUILD FLOOR PAINT AG36

Features:

A hard wearing, contract grade two pack floor finish, which has excellent water and wear resistance. Ideal for application to metal and concrete floors. This paint should not be applied over PVA sealer, latex self leveling compound or power floated concrete. Made for large, price sensitive projects. Please contact our Technical Department.

Availability:

Minimum 25 Litres in 5 Litre packs containing 4 Litres Base and 1 Litre Catalyst/Hardener in Mid & Dark Grey. AG37 Contract Grade Two Pack Epoxy High Build Non-slip Floor Finish also available. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

58% $\pm$ 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. Concrete floors must be at least 6 months old before painting. On existing painted floors it is advisable to paint a test patch to check compatibility. For newer concrete, please contact our Technical Department.

Application:

Brush or roller. Mix AG36 Floor Finish Two Pack Epoxy base 4 to 1 by volume with AGC36/70 Hardener and thin the mixed paint up to 10% by volume with ATR114 Two Pack Epoxy Thinners. Allow to stand for 10 minutes before use. Pot life when mixed: 8 hours @ 20°C.

Coverage:

Approximately 30 sq metres per 5 Litres per coat.

Drying:

Touch dry:	4 hours @ 20°C.
Hard dry:	12 hours @ 20°C.
Full cure:	24 - 48 hours depending on temperature.

Health & Safety: Please see MSDS sheet **100E5BC**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

AG36 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.