



# TECHNICAL PAINT SERVICES

## AP80/20 RED LEAD PRIMER TYPE "B"

### **Features:**

An oil based primer for iron and steel, containing over 80% lead pigment, conforming to BS 2523 Type "B". Typical applications would be structural and marine steelwork, bridges and gantries, where a thick film is required for protection awaiting further priming and finishing coats.

Lead based paint systems can only be re-used onto approved Listed Heritage structures as controlled by English Heritage. Individuals who wish to obtain paints for qualifying structures or artworks must complete a DEFRA declaration form which can be downloaded from our website. Lead Regulations apply. Please note our products are made to order and it may take 5-7 days before shipping.

### **Availability:**

In 5.0 Litre containers. Please note that our products are made to order and it may therefore take up to 7-10 days before shipping.

### **Volume Solids:**

84% ± 3% (BS 3900 Part A10).

### **Preparation:**

The substrate must be thoroughly clean, dry and free from corrosion, mill scale, dust and grease. Stir the primer thoroughly before use.

### **Application:**

By brush or roller. Supplied ready for use for brushing. Use White Spirit for cleaning. Apply immediately after cleaning, brushing well in to the surface to fill any imperfections or pin holes. DO NOT SPRAY.

### **Coverage:**

Approximately 55 sq metres per 5.0 Litres.

### **Drying:**

Touch dry: 8 - 12 hours @ 20°C.

Recoatable: 48 hours minimum.

**Health & Safety:** Please see MSDS sheet 100V17.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

AP80/20 04

14

## FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.