

TECHNICAL PAINT SERVICES

AS147 SQUASH COURT ACRYLIC PRIMER, WHITE

Features:

This water-based 100% pure acrylic primer is suitable for all types of substrate. Ideal for sealing plastered walls as a base for A147 Squash Court Eggshell Finish, White or Colours.

Availability:

In 5.0 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

 $45\%\pm3\%$ (BS 3900 Part A10).

Preparation:

The substrate must be cleaned, dry and free from dust and grease. *Plaster must be thoroughly dry* and any imperfect surfaces must be made good before application of AS147.

Application:

Brush, roller, conventional or airless spray. For optimum results, AS147 should be thinned approximately 25% with clean tap water to aid penetration of porous surfaces. It is recommended that two coats are applied to previously un-treated porous surfaces, allowing 2 hours drying between coats.

Coverage: Approximately 50 sq metres per 5.0 Litres depending on the porosity of the substrate.

Drying:

Touch dry:30 minutes @ 20°C.Hard dry & recoatable:2 hours @ 20°C.

Health & Safety: Please see MSDS sheet 100C3.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

AS147 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.