B1/11 HEAVY BODIED BLACK BITUMEN

Features:

An extremely flexible and waterproof coating suitable for application to slate, tile and asphalt roofs where leakage is a problem or where extra protection is required. Its structural strength also makes it suitable for boat hulls, cabin decking, gutters and general maintenance.

Availability:

5 Litre containers. Please note that our products are made to order and it may therefore take up to 5 days before shipping.

Volume Solids:

 $60\% \pm 2\%$ (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease. Previously painted surfaces should be rubbed down and treated with a suitable metal primer.

Application:

Brush or roller. May be applied over RP10 Chlorinated Rubber Primer, AP79 Universal Primer or UP89 Two Pack Etching Primer. Thinning is not normally necessary, but brushes etc should be cleaned with White Spirit.

Coverage:

Approximately 20 sq metres per 5 Litres.

Drying:

Overnight.

Health & Safety: Please see MSDS sheet 100B2.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

B111 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.