

BS1/60 BITUMEN AND CREOSOTE SEALER ALUMINIUM

Features:

A spirit-based sealer designed to seal stains on surfaces previously treated with creosote, asphalt, tar or soaked in oil. Recoating with Synthetic, Oil based, Chlorinated Rubber or Two Pack systems may then be undertaken without fear of "bleeding".

Availability:

5 and 2.5 Litre containers. Please note that our products are made to order and it may therefore take 5-7 days before shipping.

Volume Solids:

 $25\% \pm 3\%$ (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

Application:

Brush or roller only (Thermally bonded rollers are recommended). Supplied ready for use and should not be thinned. Normal only one coat should be necessary but where very bad contamination is present then a second coat maybe needed. All tools should be cleaned with methylated sprits only

Coverage:

Approximately 40 sq. metres per 5 Litres.

Drying:

Approximately 2 hours @ 20°C.

Health & Safety: Please see MSDS sheet 100F6.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

BS160 02 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.