



TECHNICAL PAINT SERVICES

E27 100% ACRYLIC EMULSION

Features:

A water based 100% pure Acrylic Emulsion, suitable for application to all types of porous substrates, exhibiting excellent water resistance and exterior durability. Also suitable as a coating on walls around and within a swimming pool environment (pool halls etc).

Availability:

BS4800 & BS381 colour ranges plus Black and White in 5 Litre containers in matt or satin finish. Limited RAL colours also made to order, 5 Litres minimum. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust and grease. Where a previously painted or unstable surface exists, or when a strong colour change is required, surfaces must be stripped or sealed with WB1010 Primer prior to application. For all other surfaces or where you are unsure of the correct procedure, please call our Technical Team for assistance.

Application:

Brush, roller, conventional or airless spray. On all new porous surfaces apply a coat of EP27 Acrylic Emulsion Primer and allow to fully dry as per data sheet. It is then recommended that two full coats of E27 100% Acrylic be applied over the primer; some dark and strong colours may need additional coats. E27 is supplied ready for use for brushing and rolling, allowing 2 hours drying between coats. For conventional or airless spray, please contact our Technical team.

Coverage:

Approximately 40-50 sq metres per 5 Litres, depending on porosity of substrate.

Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

Health & Safety: Please see MSDS sheet **100C3**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

E27 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.