



TECHNICAL PAINT SERVICES

E27 100% ACRYLIC EMULSION

Features:

A water based 100% pure acrylic emulsion, suitable for application to all types of porous substrates, exhibiting excellent water resistance and exterior durability. Also suitable as a coating for inside concrete swimming pools, ponds, pool walls and ceilings.

Availability:

BS4800 colour range plus Black and White in 5, 2.5 and 1 Litre containers in matt or satin finish. Limited RAL colours to order, 5 Litres minimum.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust and grease. Where a previously painted or unstable surface exists, or when a strong colour change is required, surfaces must be stripped or sealed with WB1010 Primer prior to application.

Application:

Brush, roller, conventional or airless spray. Supplied ready for use for brushing and rolling. On all new surfaces a thinned first coat should be applied using clean tap water for thinning up to 15% by volume. Alternatively, a coat of WB1010 Primer should be applied and allowed to fully dry. It is then recommended that two full coats be applied to the surface, allowing 2 hours drying between coats.

Coverage:

Approximately 50 sq metres per 5 Litres, depending on porosity of substrate.

Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.

See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.