



TECHNICAL PAINT SERVICES

E28 BLACK-OUT ACRYLIC MATT FINISH

Features:

A dense water based matt finish, suitable for application in to ceiling voids to hide an assortment of services including cables, cable and network housing, trunking, piping work etc. Can also be applied to most metal and powder coated surfaces after suitable priming. Other surfaces can include cement rendering, cementitious boards, aqua board, concrete and some brickwork, but not Engineering or Fletton bricks. Virtually V.O.C. free.

Availability:

In RAL 9011 Graphite Black in 5 Litres. Other colours also available in minimum of 100 Litre batches. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

65% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease. Previously unpainted or porous surfaces should be treated with one coat of WBP1010 Primer, allowed to dry thoroughly before coating with E28.

Application:

By brush, roller or airless spray. Thin up to 10- 20% by volume with water for spraying. Allow suitable drying time between coats.

Coverage:

Approximately 25-30sq. metres per 5 Litres per coat, depending on porosity of surface and surface profile.

Drying:

| | |
|-------------|---------------------------------------|
| Touch dry: | 2 hours @ 20°C. |
| Recoatable: | 4-6 Hours @ 20°C. |
| Full Dry: | 24-48 hours. Depending on temperature |

Health & Safety: Please see MSDS sheet **100C3**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

E28 02 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.