



# TECHNICAL PAINT SERVICES

## EP27 100% ACRYLIC EMULSION PRIMER

### **Features:**

A special formulated water based primer used as a base coat for E27 Acrylic Emulsion, designed to give a uniform base and eliminate “grinning” of the substrate thus producing a more uniformed finish. For use on porous surfaces such as all forms of moisture resistant boards, aqua board, plaster boards, plaster skims, cement render, asbestos and most forms of bricks but not Common or Engineering.

### **Availability:**

5 Litre containers in Creamy White only. Other colours made to order in minimum of 25 Litres to suit dark or brightly coloured topcoats. Please note our products are made to order and it may take 5-7 days before shipping.

### **Volume Solids:**

24% ± 3% (BS 3900 Part A10).

### **Preparation:**

The surface should be thoroughly clean, and free from dust and grease.

### **Application:**

Brush, roller or airless spray. Supplied ready for use. To aid penetration of very absorbent surfaces, it is recommended that a first coat is applied thinned up to 20% by volume with clean tap water.

### **Coverage:**

Approximately 40-50 sq. metres per 5 Litres depending on porosity of substrate.

### **Drying:**

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

**Health & Safety:** Please see MSDS sheet **100C3**.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

EP27 02 15

**FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.**

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email [enquiries@technicalpaintservices.co.uk](mailto:enquiries@technicalpaintservices.co.uk) [www.technicalpaintservices.co.uk](http://www.technicalpaintservices.co.uk)

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.