# ML55/70/1 YACHT VARNISH

### Features:

A high quality varnish based on alkyd resin, specially formulated to meet the exacting demands of a marine environment. This varnish has excellent resistance to intense sunlight and salt water, whilst providing a durable, protective coating and enhancing the natural appearance of wood.

## Availability:

In 5 and 2.5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

#### Volume Solids:

 $53\% \pm 3\%$  (BS 3900 Part A10). May vary with colour.

### Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease. Remove any wax with White Spirit and sand down to a smooth finish.

### Application:

Brush or roller. Supplied ready for use for brushing. Use White Spirit for cleaning. On previously untreated wood, it is advisable to thin the first coat up to 20% by volume with White Spirit to aid penetration and seal the wood. It is recommended that two coats are applied to sealed wood.

## Coverage:

Approximately 60 sq metres per 5 Litres per coat.

## Drying:

Touch dry: 3 hours @ 20°C. Hard dry: 8 hours @ 20°C.

Health & Safety: Please see MSDS sheet 100D4.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

ML55 04 14

# FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.