



TECHNICAL PAINT SERVICES

R10 CHLORINATED RUBBER PAINT

Features:

An air drying, single pack system resistant to a wide range of chemicals, including acids, alkalis, oxidising agents, inorganic salts, moist gases and mineral oil. Having excellent exterior durability and heat resistance up to 75°C, R10 is ideally suited for application to chemical storage tanks, bridges, marine equipment, swimming pool surrounding walls and ceilings, sewage tanks etc. R10 is also suitable for application to newly laid concrete which has been allowed to weather for 3 - 4 weeks.

Availability:

BS4800 colour range made to order in 5 Litre containers. A limited RAL range is offered, minimum 5 Litres. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

51% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be clean, dry and free from corrosion, dust and grease. R10 may be applied over RP10 Chlorinated Rubber Primer, AP79 Universal Primer, UP89 Two Pack Etching Primer, WBP1010 Universal Primer or WBP1020 Two Pack Epoxy Primer.

Application:

Brush, roller, or airless spray. Supplied ready for use for brushing. Thin up to 20% by volume with UTR112 Universal Synthetic Thinners to achieve a spraying viscosity of 30 seconds BSB4 cup @ 20°C. We recommend a 1.9 Thou' airless tip size at 2000psi.

Coverage:

40 sq. metres per 5 Litres depending on surface profile.

Drying:

Touch dry:	30 - 40 minutes @ 20°C. 3 hours @ 10°C.
Recoatable:	8 hours @ 20°C. 12 hours @ 10°C.

Health & Safety: Please see MSDS sheet **10019**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

R10 02 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.