



TECHNICAL PAINT SERVICES

R1007 ACRYLATED RUBBER FINISH

Features:

A fast drying newly modified, soft solvented single pack finish, specially re-formulated for ease of application. This product has mild resistance to a wide range of chemicals, including acids, alkalis, inorganic salts, mineral oil and water. Ideally suited for application to pool halls on moisture resistant board, plaster, brick or block work, where a more robust finish is needed or where the surface is likely to come in contact with pool water or higher than normal humidity. Suitable for general industrial situations, plant and moist conditions and can be used on wood and various metals via a suitable primer.

Availability:

Made to order in most of the BS4800 colour range, in 5 Litre containers. A limited range of RAL colours can be made to order, minimum 50 Litre lots. RP1007 Acrylated Rubber Undercoat also available. Please note our products are made to order and it may take up to 7 days before shipping.

Volume Solids:

51%±3% (BS 3900 Part A10).

Preparation:

The surface should be clean, dry and free from dust and grease.

Surface priming:

All surfaces should be primed with a suitable primer as below. For all other surfaces please contact our Technical Team.

Plaster, Aqua or moisture resistant board, brick or block work surfaces: apply a coat of WBP1010 Primer.
Metal surfaces: Apply a coat of a suitable primer followed by RP1007 Undercoat.

Application:

Brush, roller or airless spray. Supplied ready for use for brushing. Thin R1007 up to 25% by volume with UTR112 Universal Synthetic Thinners to achieve a suitable spraying viscosity. We recommend a 1.9 Thou' airless tip size at 2000psi.

Coverage:

40 - 50 sq metres per 5 Litres depending on surface profile @ 25 microns dry film thickness.

Drying:

Touch dry: 1 hour @ 20°C. 3 Hours @ 10°C.

Recoatable: 8 hours @ 20°C. 12 hours @ 10°C.

Health & Safety: Please see MSDS sheet **100D4**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

R1007 01 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.