



TECHNICAL PAINT SERVICES

RLP80 RED LEAD POWDER

Features:

Red Lead Powder is a very popular traditional marine product. A bright orange powder with strong preservative properties. When mixed with Linseed Oil Putty, Red Lead Putty is created for use on wooden craft as a stopper in seams below the waterline.

Availability:

5 Kg containers only.

Volume Solids:

N/A.

Preparation:

Appropriate proportions are 16 parts of Linseed Oil Putty to 1 part Red Lead Powder, with Linseed Oil added to modify the consistency.

Application:

N/A.

Coverage:

N/A.

Drying:

N/A.

Health & Safety: Please see MSDS sheet **MSDSRLP80**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

RLP80 03 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.