



TECHNICAL PAINT SERVICES

RP10 CHLORINATED RUBBER PRIMER

Features:

A fast drying Chlorinated Rubber based primer, pigmented with Zinc Phosphate, affording good abrasion resistance and anti-corrosive properties. Also suitable for use as a primer for newly plastered walls or dry lining. Forms an ideal base for R10 Chlorinated Rubber Paint.

Availability:

Grey & Light Grey in 5 Litre containers. Other colours to order, minimum 25 Litres. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

50% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be clean, dry and free from corrosion, dust and grease. Aluminium should be coated with UP89 Two Pack Etching Primer prior to application of RP10. For plastic use PP129 Adhesion Promoter.

Application:

Brush, conventional or airless spray. Supplied ready for use for brushing. Thin up to 25% by volume with UTR112 Universal Synthetic Thinners to achieve a spraying viscosity of 25 - 30 seconds BSB4 cup @ 20°C. We recommend a 1.9 Thou' airless tip size at 2000psi. For new plaster thin by 15% by volume.

Coverage:

40 sq metres per 5 Litres giving a dry film thickness of 50 microns.

Drying:

Touch dry: 30 - 40 minutes @ 20°C.

Recoating time: Minimum of 8 hours @ 20°C.

Health & Safety: Please see MSDS sheet **10019**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

RP10 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.