



# TECHNICAL PAINT SERVICES

## WB1004 BRICK TONER

### **Features:**

Brick Toner is a water based, environmentally friendly, non-toxic coating which will age the appearance of new brick to create a matched or aged look to your existing bricks. Brick Toner can also be used on stone, concrete, non glazed tiles and other surfaces. Will darken new surfaces that may set into a mature outdoor environment and will last for many years, continuing to age naturally.

### **Availability:**

5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

### **Volume Solids:**

15% + 3% (BS 3900 Part A10).

### **Preparation:**

Before use, make sure all surfaces are clean, dry and dust free. Remove all plants and adjacent garden furniture. We recommend that gloves and protective goggles are worn, avoiding contact with the skin. Test a small area and allow to dry for 5 minutes. If the effect is too dark, dilute Brick Toner as necessary with clean tap water. If too light, apply a second coat. Brick Toner can be sprayed, brushed or sponge applied depending on the surface to be stained. Any simple hand spray can be used. Avoid application if rain or showers are imminent. Clean all brushes and other equipment with water.

### **Coverage:**

Approximately 8 sq metres per Litre depending on surface porosity.

### **Drying:**

Touch dry:	5 minutes @ 20°C.
Recoatable:	2 hours.
Fully cured:	24 hours.

**Health & Safety:** Please see MSDS sheet **100C3**.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

WB1004 04 14

**FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.**

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255  
Email [enquiries@technicalpaintservices.co.uk](mailto:enquiries@technicalpaintservices.co.uk) [www.technicalpaintservices.co.uk](http://www.technicalpaintservices.co.uk)

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.