



TECHNICAL PAINT SERVICES

WB178 WATER BASED ACRYLIC GLOSS PAINT

Features:

A water based gloss paint based on acrylic resin, affording a tough durable finish on a wide range of substrates. Also available as an anti-fungal finish. Suitable for application to wood, ferrous and non-ferrous metals, plaster, concrete and most types of plastic. Low odour, non-flammable and virtually no VOC emissions. For best results use WBP1010 Primer.

Availability:

BS4800 colour range in 5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

Surfaces must be sound, clean, dry and free from wax, grease, oil and loose particles. Porous substrates such as plaster and plasterboard should be treated with stabilising solution before finishing. On existing painted surfaces, remove all loose and flaking paint and thoroughly rub down with abrasive paper. Any bare surfaces should be primed with suitable primer as necessary. For best results use WBP1010 Primer.

Application:

Stir thoroughly and check colour before use. Apply by brush, roller or spray. If it is to be applied in areas of constant humidity, such as indoor swimming pools and conservatories, please contact our Technical Team. Do not apply at temperatures below 8°C or when raining or foggy.

Coverage:

Approximately 12 - 15 sq metres per Litre.

Drying:

Touch dry: 15 - 20 minutes @ 20°C.
Hard dry: 2 hours.
Recoatible: 4 hours.

Health & Safety: Please see MSDS sheet **100C3**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

WB178 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.