



# TECHNICAL PAINT SERVICES

## WBF42 100% ACRYLIC EMULSION FLUORESCENT FINISH

### **Features:**

A water based 100% pure acrylic fluorescent paint. A special range of vivid safety marking paints ideal for use in poorly lit areas. Suitable for application to a wide range of substrates after suitable priming with WBF42 Basecoat White. Requires a source of daylight, moonlight or artificial light to be effective. This coating has been specially formulated to react with most wavelengths of U.V. light and is ideal for use in nightclubs, children's bedrooms or playrooms.

### **Availability:**

WBF42 Colour range: Purple, White, Dark Red, Light Red, Light Yellow, Dark Green, Light Green, Blue, Light Orange, Dark Orange and Pink. 5.0 and 2.5 Litre containers in a Matt finish. Please note our products are made to order and it may take 5-7 days before shipping.

### **Volume Solids:**

45% ± 3% (BS 3900 Part A10).

### **Preparation:**

The surface should be thoroughly clean, dry and free from dust and grease. Apply over WBF42 Fluorescent Basecoat White.

### **Application:**

It is highly recommended that this product is applied by conventional or airless spray for consistency of colour and to avoid brush marks. Small areas can be brushed or rolled but this can cause unevenness in colour. Use clean tap water for thinning, if required and cleaning. It is recommended that two coats be applied to primed surfaces, allowing 2 hours drying between coats. Must be over coated with WBF42/70/4 Clear Overcoat.

### **Coverage:**

Approximately 50 sq metres per 5 Litre, depending on porosity of substrate.

### **Drying:**

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

**Health & Safety:** Please see MSDS sheet **100C3**.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

WBF42 04 14

**FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.**

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email [enquiries@technicalpaintservices.co.uk](mailto:enquiries@technicalpaintservices.co.uk) [www.technicalpaintservices.co.uk](http://www.technicalpaintservices.co.uk)

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.