



TECHNICAL PAINT SERVICES

WBFP42 EMULSION 100% ACRYLIC FLUORESCENT BASECOAT WHITE

Features:

A water based 100% pure acrylic emulsion, exhibiting excellent exterior durability, suitable for application to a wide range of substrates. Contains a high proportion of titanium dioxide, thus giving excellent reflective and non-fade properties. To be used as a basecoat for WBF42 Acrylic Fluorescent Paint.

Availability:

5.0 and 2.5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

45% ± 3% (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust and grease. Previously painted surfaces must be stripped, thoroughly rubbed down with abrasive paper and cleaned prior to application. Specialist primers will be required for different substrates; please contact our Technical Team for help.

Application:

Brush, roller, conventional or airless spray. Use clean tap water for thinning, if required and cleaning. It is recommended that two coats are applied to previously untreated surfaces, allowing 2 hours drying between coats.

Coverage:

Approximately 50 sq metres per 5 Litres depending on porosity of substrate.

Drying:

Touch dry: 30 minutes @ 20°C.

Hard dry & recoatable: 2 hours @ 20°C.

Health & Safety: Please see MSDS sheet **100C3**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

WBFP42 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.