



TECHNICAL PAINT SERVICES

X85 MORDANT SOLUTION

Features:

A pre-treatment for new, galvanised surfaces. The treatment etches the surface of the metal to provide a key for subsequent coats of paint and varnish.

Availability:

5, 2.5 and 1 Litre containers.

Volume Solids:

N/A.

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

Application:

Brush liberally onto galvanised surfaces and leave for 1 hour for the solution to react. A black deposit will be formed when the reaction is complete. The surface should then be washed off with clean tap water to remove any zinc salts and dried thoroughly before the application of a primer, which should be applied within 2 hours.

Coverage:

Approximately 100 sq metres per 5 Litres.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control.

See Standard Conditions of Sale.

Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 0845 230 1244 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.com

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.