



TECHNICAL PAINT SERVICES

LM149 TENNIS COURT LINE MARKING COATING

Features:

A special designed acrylic based line marking coating, designed for application to asphalt, macadam and concrete tennis courts and Multi Use Games Areas (MUGAs). Can be supplied with a non-slip additive if needed.

Availability:

Standard Colours in 5 Litres: White, Black, Yellow, Red, Green, Blue, Orange. All other BS4800 colours available to special order in 5 Litre containers minimum 20 Litre mix. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

35% ± 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from loose flaking material, dirt, grease and vegetative growth.

Application:

By brush roller or airless spray on to a dry surface do don't apply in damp or when there is the likelihood of rain. Supplied ready for use for brushing and rolling, can also be sprayed by airless spray but will need to be thinned up to 15% with clean fresh tap water. When applied by roller, a lower spreading rate will be obtained. Two coats will normally need to be applied, allowing suitable drying between coats. Use clean tap water for cleaning tools.

Coverage:

20 - 30 sq metres per 5 Litres depending on method of application and porosity of surface.

Drying:

Surface Dry: 1 - 2 hours @ 20°C.

Recoatable: 4 hours @ 20°C.

Health & Safety: Please see MSDS sheet **100C3**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

LM149 02 16

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOLE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255

Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.