A146/60 SOLAR REFLECTING BITUMINOUS HEAVY BODIED

Features:

A high build, solar reflecting and water proofing bituminous aluminium coating designed for use as a finishing coat over bitumen and concrete roofing and primed steel. May be used as a base coat for A146/61 Solar Reflecting Aluminium to increase build and protection.

Availability:

In 5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

 $60\% \pm 3\%$ (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

Application:

Brush, roller, or conventional spray. Thinning is not normally required. Use White Spirit for cleaning.

Note:

Some difference in brightness and general appearance may be anticipated between brush, roller and spray application, and therefore mixed methods of application are not recommended.

Coverage:

Approximately 35 - 40 sq metres per 5 Litres per coat.

Drying:

Touch dry: 2 hours @ 20°C. Recoatable: 12 hours @ 20°C.

Health & Safety: Please see MSDS sheet 100B2.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

A14660 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.