

A149 TENNIS COURT PAINT

Features:

An acrylic based low gloss paint, designed for application to asphalt, macadam and concrete tennis courts and Multi Use Games Areas (MUGAs). Can be supplied with a non-slip additive.

Availability:

All BS4800 colours plus Black and White in 5 Litre containers. Other colours to order. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

 $35\% \pm 3\%$ (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from loose flaking material, dirt, grease and vegetative growth.

Application:

By brush or roller. Supplied ready for use for brushing. Use clean tap water for cleaning. When applied by roller, a lower spreading rate will be obtained.

Coverage:

20 - 30 sq metres per 5 Litres depending on method of application and porosity of surface.

Drying:

Surface Dry: 1 - 2 hours @ 20°C. Recoatable: 4 hours @ 20°C.

Health & Safety: Please see MSDS sheet 100C3.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

A149 04 14

FOR PROFESSIONAL USE ONLY, READ DATA BEFORE USE.