

# **A5 ANTI-GLARE SOLVENT BASED**

#### Features:

A translucent coating designed to reduce the intensity of sunlight transmitted through glass or Perspex windows. It is suitable for interior or exterior use. A5 has good durability, being able to withstand the extremes of both winter and summer weather. Easily removed with White Spirit if required.

### Availability:

Off-White and Green in 5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

### **Volume Solids:**

 $25\% \pm 3\%$  (BS 3900 Part A10).

### Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

### Application:

Brush or spray directly onto the substrate. Only one coat is normally required. Supplied ready for use but if necessary, thin with White Spirit.

## Coverage:

Approximately 60 - 70 sq metres per 5 Litres per coat.

## Drying:

Approximately 6 - 8 hours @ 20°C.

Health & Safety: Please see MSDS sheet 100D4.

**Note:** For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

A5 04 14

## FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.