



TECHNICAL PAINT SERVICES

AG1 CONTRACT GRADE BITUMINOUS COLOURS

Features:

A budget blend of refined bitumen and alkyd resins, designed to give good water proofing qualities for large structural steel items, farm buildings, tanks, silos etc.

Availability:

A selection of darker shades from the BS4800 range of colours, minimum 100 Litres. Please note that our products are made to order and it may therefore take 5-7 days before shipping.

Volume Solids:

50% ± 3% (BS 3900 Part A10). Will vary with colour.

Preparation:

The substrate must be thoroughly clean, dry and free from oil and grease. May be applied directly to cleaned surfaces. Extended durability may be achieved by the use of APG79 Contract Primer prior to finishing.

Application:

Brush, roller, conventional or airless spray. Use UTR112 Universal Synthetic Thinners if required. Clean equipment with White Spirit.

Coverage:

Approximately 40 sq metres per 5 Litres per coat, when brushed.

Drying:

Touch dry: 30 minutes.
Recoatable: 12 hours @ 20°C.

Health & Safety: Please see MSDS sheet **100B2**.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

AG1 02 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.