H46/60 LOW TEMPERATURE HEAT RESISTING ALUMINIUM

Features:

A synthetic resin based bright aluminium finish, ideally suited to the coating of flues and boilers. Provides a durable, water resistant finish capable of withstanding temperatures up to 180°C.

Availability:

5.0 Litre and 2.5 Litre containers only. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

 $50\% \pm 3\%$ (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from corrosion, dust and grease.

Application:

Do not apply to heated surfaces, cool before applying by brush, roller, conventional or airless spray. Thin up to 20% by volume, using UTR112 Universal Synthetic Thinners to achieve a spraying viscosity of 25 - 30 seconds BSB4 cup @ 20°C. Two coats are recommended to achieve a minimum dry film thickness of 50 microns.

Coverage:

Approximately 35 - 40 sq metres per 5 Litres depending on surface profile.

Drying:

Touch dry: 3 - 4 hours @ 20°C.

Hard dry & recoatable: Overnight.

Health & Safety: Please see MSDS sheet 100D4.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

H4660 02 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.