

RP1007 ACRYLATED RUBBER UNDERCOAT

Features:

A newly modified soft solvated undercoat for use as a suitable base and to add grip and build to the surface followed by subsequent application of R1007 Acrylated Rubber System.

Availability:

5 Litre containers in Light and Mid Grey as standard. Other colours available to suit finish. Please note our products are made to order and it may take up to 7 days before shipping.

Volume Solids:

55 % +3% (BS 3900 Part A10).

Preparation:

Surface should be clean, dry and sound. For all new metal and timber surfaces apply a suitable primer, for surfaces other than above please contact our Technical Department for guidance.

Application:

By brush, roller, conventional or airless spray. Thin as required using UTR112 Thinners. We recommend a 1.9 Thou' airless tip size at 2000psi.

Coverage:

Approximately 40 - 50 metres per 5 Litres depending on the surface profile.

Drying:

Touch dry: 1/2 hour @ 20°C. Recoatable: 6- 8 hours@ 20°C.

Fully cured: 24 hours.

Health & Safety: Please see MSDS sheet 100D4.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

RP1007 01 15

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.