WBFS42 EMULSION 100% ACRYLIC CLEAR OVERCOAT/LACQUER

Features:

A water based sealer, stabiliser and barrier coat based on acrylic copolymer. Suitable for application over WBF42 Fluorescent colours.

Availability:

5.0 and 2.5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

 $60\% \pm 3\%$ (BS 3900 Part A10).

Preparation:

The surface should be thoroughly clean, dry and free from dust and grease. Leave at least 24 hours before applying over the last coat of WBF42 finishing coat.

Application:

Brush, roller or spray. Use clean tap water for thinning and cleaning.

Coverage:

Approximately 40 - 50 sq metres per 5 Litres.

Drying:

Touch dry: 30 minutes @ 20°C. Hard dry & recoatable: 2 hours @ 20°C.

Note:

Thorough drying is indicated by the original opaque appearance becoming clear.

Health & Safety: Please see MSDS sheet 100C3.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

WBFS42 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.